
<u>Package 1 Basic</u>	<u>Forward Channel ONLY</u>	<u>Techn. Data:</u>		
1 pc.	Link XP Transmitter	TX frequency	1,9 - 2,6 GHz	frequency agile
		TX power	10-50-100 mW	
		Modulation	QPSK, 16-QAM, 64-QAM	
		Video IN	CCVS <u>or</u> Y/U/V Component	
		Audio IN	2 x analog	
		<u>alternatively</u>		
		Video IN	SDI	
		Audio IN	4 x analog	
		Battery mount	für XDE-Akkus (V-mount)	
1 pc.	TX antenne with that	Frequency range	1,9 - 2,6 GHz	
1 pc.	Link Receiver	Receiver	4-way (!) Diversity	
		RX frequency	1,9 - 2,6 GHz	frequency agile
		Modulation	QPSK, 16-QAM, 64-QAM	adjustable
		Video OUT	CCVS	
		Audio OUT	2 x analog	
		<u>alternatively</u>		
		Video OUT	SDI	
		Audio OUT	4 x analog	
		Frame Lock IN		for synchronization
4 pc.	Downconverter/Filter	LO-Frequency	1.840 MHz	
2 pc.	360° RX antennas	Frequency range	1,9 - 2,6 GHz	
2 pc.	180° RX antennas	Frequency range	1,9 - 2,6 GHz	
4 pc.	Antenna cables	Length	up to 100m each	upon request

Package 2 Full Fwd. AND Return Channel **Techn. Data:**

Features:
controls virtually all functions of a portable camera, such as:
Iris, Black level, White Balance, Black Balance, Gamma, ABB, WBB,
Shutter Speeds, Tally, Color Bar, etc.
RETURN VIDEO in Camera Viewfinder !
Intercom

Equipment as in Package 1 Basic, but additionally: :

1 pc. Camera SONY DXC-D30 incl.Interface CA-511

OTHER CAMERA MAKES UPON REQUEST !

1 pc.	Camera Back with that	Return reception RX frequency	Control signals from the XPe-transmitter 1,9 - 2,6 GHz	frequency agile
1 pc.	360° RX antenna	Frequency range	1,9 - 2,6 GHz	
1 pc.	OCP	Control Panel	with Joystick	
1 pc.	Link XPe transmitter	TX frequency TX power	1,9 - 2,6 GHz 10-50-100 mW	frequency agile
		Video IN	CCVS	
		Audio IN	2 x analog	
1 pc.	TX antenne with that	Frequency range	1,9 - 2,6 GHz	
various	Cables for that			

Package 3	Economy	Forward Channel ONLY	Techn. Data:	
1 pc.	Link XP Transmitter	TX frequency TX power	1,9 - 2,6 GHz 10-50-100 mW	frequency agile
		Video IN Audio IN	CCVS only 2 x analog	
1 pc.	TX antenne with that	Frequency range	1,9 - 2,6 GHz	
1 pc.	Link Receiver	Receiver RX frequency	Diversity 1,9 - 2,6 GHz	frequency agile
		Video OUT Audio OUT <u>alternatively</u> Video OUT	CCVS 2 x analog SDI	
		Frame Lock IN		for synchronization
2 pcs.	Downconverter/Filter	LO-Frequency	1,840 MHz	
2 pcs.	360° RX antennas	Frequency range	1,9 - 2,6 GHz	
2 pcs.	<u>or</u> 180° RX antennas	Frequency range	1,9 - 2,6 GHz	
2 pcs.	Antenna cables	Length	up to 100m each	upon request
